



# TeSi®

**A COMPANY OF TESI GROUP**

[info@tesigroup.com](mailto:info@tesigroup.com)  
[www.tesigroup.com](http://www.tesigroup.com)



**TESI SPA  
 HEADQUARTER**

Via Piave, 20/11 20080 - Vermezzo (MI) ITALY  
 Tel +39 02 9440501 - Fax +39 02 9449087

**TESIGROUP LLC**

10617 Jefferson Chemical Road  
 Conroe, TX 77301 USA  
 Tel +1 (936) 4415678 - Fax +1 (936) 7565566

**INDUCTION HEATING CENTRE**

Via San Giuseppe 29 43039 - Salsomaggiore Terme (PR) ITALY

**DAEMAR HEATING TECHNOLOGY CO.ltd**

Unit 501, Building 1 - Jia 12 Jiuxianqiao Road  
 Chaoyang District, Beijing CHINA  
 Tel +86 10 6438 0812 - Fax +86 10 6438 0612

## Induction Heating Generators— TacGT 系列



TacGT 系列选型表:

型号:	TacGT-25	TacGT-25Twin	TacGT-40	TacGT-40 Twin	TacGT-80	TacGT-80 Twin
最大输出功率:	25KW	25KW*2	40KW	40KW*2	80KW	80KW*2
输入电压:	380V±20%	380V±20%	380V±20%	380V±20%	380V±20%	380V±20%
输入电流:	42A	42A*2	67A	67A*2	135A	135A*2
输入频率:	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
设备重量:	80Kg	120Kg	95Kg	140Kg	180Kg	270Kg
防护等级:	IP54	IP54	IP54	IP54	IP54	IP54
冷却方式:	水冷	水冷	水冷	水冷	水冷	水冷
感应线圈:	定制	定制	定制	定制	定制	定制
手持变压器重量:	约 2.5Kg	约 2.5Kg	约 3.3Kg	约 3.3Kg	约 5.5Kg	约 5.5Kg
通信接口:	RS232/485	RS232/485	RS232/485	RS232/485	RS232/485	RS232/485
功率调节方式:	1-100%无级可调	1-100%无级可调	1-100%无级可调	1-100%无级可调	1-100%无级可调	1-100%无级可调
冷却水入口温度:	Max.35℃	Max.35℃	Max.35℃	Max.35℃	Max.35℃	Max.35℃
冷却水最小水流量:	6L/min	12L/min	12L/min	24L/min	23L/min	2*23L/min
柔性电缆长度:	5/10/20m	5/10/20m	5/10/20m	5/10/20m	5/10/20m	5/10/20m
工作频率:	10-25KHz	10-25KHz	10-25KHz	10-25KHz	10-25KHz	10-25KHz
功率因素:	≥0.95	≥0.95	≥0.95	≥0.95	≥0.95	≥0.95
效率:	≥93%	≥93%	≥93%	≥93%	≥93%	≥93%
外形尺寸(长 x 宽 x 高):	700x900x1200mm	700x900x1200mm	700x900x1200mm	700x900x1200mm	870x1000x1400mm	870x1000x1400mm

