

COVALENCE[®] S1137 FILLER

Characteristics:	S1137 is a high viscosity sealant based filler material delivered on rolls.
Applications:	S1137 is used as a filler material with PERP. Filler tape is used to fill the holiday thus restoring the mill applied coating thickness of the pipe.
Product description:	S1137-XXXxYYYxZZZ XXX = Width in mm YYY = Thickness in mm ZZZ = Length in mm
Material properties:	Typical Softening point : 150°C Typical Shear strength @ 23°C (73.4°F): 0.1 N/mm ² acc. EN12068 Typical Peel strength @ 23°C (73.4°F): 1.1 N/mm acc. EN12068
Dimensions:	Width: 50 mm (2") Thickness: 3 mm (0.12") Length per roll: 3000 mm (9.8 ft)
Product printing & labeling:	No printing. Standard box label mentioning: Covalence Description , Part Number, Lot number, Quantity
Ordering info:	S1137-50x3x3000 (C6): 6 rolls per box. For PERP the filler needs to be ordered separately.

Information

Documentation	Extensive information is available on our web-site. Application instructions and other documentation can be obtained by contacting our head office, from our local distributor or by sending an email to info@sealforlife.com
Certified staff	Application of the described coating system should be carried out by certified personnel.